

## PE31

/ Three-Phase  
Inverter



### Technical Information (dependent on variant)

<b>General</b>	
Ambient temperature range	-32 to +63 °C
Type of protection	IP 66/67
Dimension	441 x 314 x 111 mm <sup>3</sup>
Volume	15.4 dm <sup>3</sup>
Weight	19 kg
<b>Electrical data</b>	
Maxium power	300 kW
Continuous power	130 kW
Nominal input voltage	750 VDC
Input voltage range	up to 800 VDC
Power semiconductor	IGBT
Phase current (peak)	450 A
Maximum switching frequency	14 kHz
Typical efficiency	97%
Supply voltage range	18 to 36 VDC
Power consumption (idling)	15 W
<b>Electrical / Signal Interfaces</b>	
AC power connection	3x M8 terminals
DC link power connection	2x M8 terminals
Signal and 28 V power supply, CAN J1939, 2 x floating digital outputs, 2 x floating digital inputs, temperature monitoring (for 6 x PT100 sensors) motor, resolver, 10-bit-resolution	MIL DTL connectors
<b>Cooling</b>	
Cooling medium	water/glycol 50/50
Nominal flow rate	13 l/min
Nominal inlet temperature	85°C
Pressure drop	0.9 Bar

#### Product benefits


- Magnet-Motor's compact automotive power inverter unit features state-of-the-art IGBT technology with efficient liquid cooling and highly sophisticated, dense packaging of circuit boards and components. Its compact size and low weight make the PE31 ideal for use as power inverters of drive motors or generators in any medium-to large-category hybrid vehicles.
- The embedded controller features high-speed digital field-oriented control, covers interfaces for various sensors and offers support for a variety of communication standards. It is appropriate for high-torque as well as for high-speed drives up to 800 VDC.



# PE31

## Technical Characteristics

- Maximum power 300 kW
- Phase current: 450 A (peak)
- Volume 15 dm<sup>3</sup>
- CAN J1939 communication
- Applicable for PM motors and generators
- Ruggedized for military vehicles
- Power outputs are short-circuit protected
- Compact and lightweight
- Diagnosis and software download via CAN bus interface



### Trusted Partner.

#### RENK Magnet-Motor GmbH

Petersbrunner Str. 2  
 82319 Starnberg  
 Germany  
 P +49 8151 262-0  
 F +49 8151 262-250  
 E [mobility.solutions@renk.com](mailto:mobility.solutions@renk.com)

Details provided about the properties and usability of the products are purely for information purposes and do not constitute a guarantee of these characteristics. The extent of goods delivered is determined by the subject matter of the specific contract. No liability accepted for errors or omissions. Subject to technical alterations. © RENK Magnet-Motor GmbH 2023